

1410 North Hilton, Soise, ID 83706-1255, (208) 334-0502

Philip E. Batt, Governor

September 18, 1995

Jerry Spray
Sandpoint Facility Manager
Louisiana-Pacific Corporation
P.O. Box 249
Sandpoint, Idaho 83864

RE: Tier II Operating Permit #017-00003 (Louisiana-Pacific Corporation, Sandpoint)
Natural Gas Boilers Modification Project

Dear Mr. Spray:

The Division of Environmental Quality (DEQ) received Louisiana-Pacific Corporation's (L-P) application for a modification to allow continuous operation of the two existing natural gas boilers at the Sandpoint facility on July 14, 1995. The application was declared complete on August 10, 1995.

The technical and regulatory analysis has been completed for this project. The requested operational increase for the natural gas boilers has been approved and the provisions and allowable emission limits affected by the modification have been altered accordingly. The text on Pages 6 and 7 of 21 and the allowable emissions in Appendix A (Tables 1 and 2 on Pages 17 and 18 of 21 in Tier II Operating Permit #017-00003) have been changed to reflect the modification. Please update your copy of Tier II Operating Permit #017-00003 by replacing the appropriate pages, as the enclosed pages supersede the permit's original pages.

Please note that the provisions and emission limits listed above have altered the Sandpoint facility's applicable requirements for Tier I permitting. Therefore, the applicable requirements and corresponding compliance certification that you have included in your Tier I Operating Permit application <u>may</u> need to be updated to reflect this.

If you have any questions regarding the terms or conditions of the enclosed permit, please contact Brian R. Monson, Bureau Chief, Operating Permits Bureau, at (208) 373-0298.

Sincerely,

orville D. Green

Assistant Administrator Permits and Enforcement

ODG\8RM\DAM:jrj...\permit\lecters\lp-ngmod.cov

Enclosure: Altered Permit Pages

cc: D. Redline, NIRO

J. Evensen, Louisiana-Pacific, Hayden Lake

Source File Mike McGown

COF

Page 6 of 21

AIR POLLUTION OPERATING PERMIT

PERMITTEE AND LOCATION

PERMIT NUMBER

Louisiana-Pacific Corporation Planing Hill Sandpoint, Idaho 017 - 00003

The Permittee is hereby allowed to operate the equipment described herein subject to the emission limits and monitoring and reporting requirements specified in this permit.

SOURCE

Natural Gas Boilers

). SOURCE DESCRIPTION

1.1 Process Description

In the event that the woodwaste boiler is shut down, two (2) natural gas boilers supply steam to the dry kilns.

1.1.1 Manufacturer: Cleaver Brooks 400 HP (XZ). Model #CB7 60-400 (XZ), Rated Capacity: 14,000 lb steam/hr (each).

1.2 Controls

Emissions from the two (2) natural gas fired boilers are uncontrolled and each vents through a separate stack.

2. EMISSION LIMITS

- 2.1 Particulate matter (PM) emissions from the two (2) natural gas fired stacks shall each not exceed 0.015 grains per standard dry cubic foot of effluent gas adjusted to three percent (3%) by volume (IDAPA 16.01.01.677), nor shall they exceed the pound per hour (lb/hr) and ton per year (T/yr) values listed in Appendix A.
- 2.2 Particulate matter emissions with aerodynamic diameters less than 10 microns (PM_{10}), carbon monoxide (CO), nitrogen oxides (NO_x), sulfur dioxide (SO_2), and volatile organic compound (VOC) emissions shall not exceed the pound per hour (1b/hr) and ton per year (T/yr) values listed in Appendix A.
- 2.3 Visible emissions from the natural gas fired boiler stacks shall not exceed twenty percent (20%) opacity for a period or periods aggregating more than three (3) minutes in any sixty (60) minute period, as determined by the Department's "Procedures Manual for Air Pollution Control" (IDAPA 16.01.01.625).

3. TESTING AND MONITORING REQUIREMENTS

- 3.1 The following information corresponding to operation shall be recorded and maintained on-site for the most recent two (2) year period:
 - 3.1.1 The total monthly natural gas usage for each of the natural gas boilers.
 - 3.1.2 Total steam production (tons) according to the following conversion factor:1400 Btu heat input per pound of steam produced.
 - 3.1.3 The total number of hours per year determined by an annual rolling average.

Recorded 9/18/95 (Date was not changed)

ISSUED: July 7, 1995 EXPIRES: July 7, 2000

DAM: jrd...\permit\lpsandpt.pmt

| Page | 7 | af | 2 |
|------|---|----|---|
| | | • | |

AIR POLLUTION OPERATING PERMIT

PERMITTEE AND LOCATION

PERMIT NUMBER

Louisiana-Pacific Corporation Planing Mill Sandpoint, Idaho

| | | | | | ****** | , | | |
|---|---|---|---|---|--------|---|---|---|
| 0 | 1 | 7 | - | 0 | 0 | 0 | 0 | 3 |

The Permittee is hereby allowed to operate the equipment described herein subject to the emission limits and monitoring and reporting requirements specified in this permit.

Natural Gas Boilers

4. REPORTING REQUIREMENTS

4.1 The Permittee shall submit hourly and annual data on operating rates to the Department in a semi-annual report.

ISSUED: July 7, 1995 EXPIRES: July 7, 2000

DAM: jrd...\permit\ipsandpt.pmt

APPENDIX A

TABLE 1

Louisiana Pacific, Sandpoint Planing Mill

PM, Emission Limits' - Hourly (lb/hr), and Annual' (T/yr)

| Source Description | Hourly PM _{is} c Emissions (lb/hr) before 7/1/96 ⁴ | Annual PM _{is} c Emissions (T/yr) before 7/1/964 | Annual PM _{is} s Emissions (lb/hr) after 7/1/96 | Annual PM ₁₆ * Emissions (T/yr) after 7/1/964 |
|------------------------------------|---|--|---|---|
| Kipper & Sons Woodwaste Boiler | 6.93 | 30.4 | 6.93 | 30.4 |
| EFB Baghouse Vent | 0.23 | 1.02 | 0.23 | 1.02 |
| Natural Gas Boiler #1 | 0.22 | 0.97 | 0.22 | 0.97 |
| Natural Gas Boiler #2 | 0.22 | 0.97 | 0.22 | 0.97 |
| Truck Bin Baghouse Vent | 1.24 | 3.86 | 1,24 | 5.42 |
| Transfer Cyclone | 1.03 | 3.21 | 1.03 | 4.51 |
| Trim Saw Cyclone | 0.51 | 1.60 | 0.00 | 0.00 |
| Lumber Drying Kilns (5 kiln rooms) | 3.04 | 13.3 | 5.1 | 22.5 |
| Woodwaste Boiler Ash Handling | 0.11 | 0.40 | 0,16 | 0.68 |
| Truck Bin Loadout Operation | 1.80 | 6.59 | 0.51 | 2.23 |
| Truck Bin Vent | 0.15 | 0.56 | 0.14 | 0.63 |
| End Coating Operation | 0.25 | 0.90 | 0.10 | 0.46 |
| Vehicle Traffic - Unpaved Areas | 0.14 | 0.52 | 0.00 | 0.00 |
| Vehicle Traffic - Paved Areas | 0.23 | 0.84 | 0.36 | 1.56 |

As determined by a pollutant specific U.S. EPA reference method, or a Department approved alternative, or as determined by the Departments's emission estimation methods used in this permit analysis.

d Or such earlier date as all required Conditional Control Measures have been completed,

ISSUED: July 7, 1995 EXPIRES: July 7, 2000

h As determined by multiplying the actual or allowable (if actual is not available) pound per hour emission rate by the allowable hours per year that the process(es) may operate(s), or by actual annual production rates.

c Includes condensables.

APPENDIX A

TABLE 2

Louisiana Pacific, Sandpoint Planing Mill

Emission Limits' - Hourly (lb/hr) and Annual' (T/yr)

| Source Description | P | ď | NG ₂ CO | | | | | yoc so, | | | |
|--------------------------------------|-------|------|--------------------|-------|------|-------|---------|-----------------|-------|-------|--|
| | lb/hr | 1/72 | 10/h | 3//46 | | | 316/165 | \$/ (¥\$ | 10/bx | #/ys | |
| 1. Kipper & Sons Woodwaste Boiler | 6.93 | 30.4 | 15.6 | 56.4 | 60.0 | 201.6 | 7,8 | 28.2 | 0.84 | 3.03 | |
| 2. Natural Gas Boiler #1 | 0,22 | 0.97 | 2.4 | 10.5 | 0.60 | 2.63 | 0.04 | 0.18 | 0.01 | 0.044 | |
| 3. Natural Gas Boiler #2 | 0.22 | 0.97 | 2.4 | 10.5 | 0.60 | 2.63 | 0.04 | 0.18 | 0.01 | 0.044 | |

a As determined by a pollutant specific U.S. EPA reference method, or a Department approved alternative, or as determined by the Departments's emission estimation methods used in this permit analysis.

c includes condensables.

ISSUED: July 7, 1995 EXPIRES: July 7, 2000

DAM: jrd...\permit\lpsandpt.pmt

b As determined by multiplying the actual or allowable (if actual is not available) pound per hour emission rate by the allowable hours per year that the process(es) may operate(s), or by actual annual production rates.